

FlexSmart® Series Readers

MIFARE® Custom Reader • 6076

ISO 14443A Contactless Smart Card Series



ACCESS interoperability.

Key Features

- ▶ **Custom Configurations** – The reader is completely configurable for every access control application challenge.
- ▶ **Open Architecture Design** – ISO 14443A compatible for card interoperability.
- ▶ **Read Flexibility** – Can read data from any MIFARE sector of the card.
- ▶ **Lifetime Warranty** on HID Cards and Readers.

The HID FlexSmart MIFARE Custom Reader is a new, flexible, highly secure and stylish contactless smart card reader ideal for customers that require a customizable reader for new or existing installations.

The HID FlexSmart MIFARE Custom Reader offers the ultimate choice in interoperability and programmability. The reader provides unique capabilities, such as reading MIFARE sectors or CSN (card serial number), to meet all your installation requirements. With the ability to read any MIFARE sectors, this reader can be configured to read any third-party formatted cards or to develop a custom format for a new application. From entry level access control to secure ID management, the reader is completely configurable for every access control application challenge.

MIFARE Advantages

The HID FlexSmart MIFARE Custom Reader can be configured to read any data within a secured MIFARE card sector when programmed with matching keys. With flexible reader programming, an HID FlexSmart Reader can define where to start reading the length of data and how the output will be formatted. The HID FlexSmart MIFARE Custom Reader complies with the requirements of ISO 14443A interoperability standards and is a perfect choice for standard encrypted ID, data storage solutions and multiple applications.

Note: To configure your requirements for HID FlexSmart MIFARE Custom Reader, please refer to the HID “How To Order Guide” and product worksheet.

Features

Mounting

The reader mounts on a door mullion or single-gang electrical box for easy installation. A red LED flashes green and the beeper sounds when reader is presented with a MIFARE® Card. The multicolor LED and beeper can also be controlled by the host system.

Diagnostics

On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper and initializes reader operation.

Durable

Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, the reader provides reliable performance and a high degree of vandal resistance.

The reader is capable of outputting in either Wiegand or Clock & Data (magnetic stripe) formatted data.

Security

MIFARE
48-bit read and write keys.
Unique key pairs may be defined for each sector.
Readers and cards must have matching keys.
All RF data transmission between the card and reader is encrypted.

Options

Colors: Black
Optional bezel styles and colors available
Selectable Output Formats
Custom label
Field Programmer
(Please see "How to Order Guide" for a description of the options and associated part numbers)

	FlexSmart® MIFARE HID Format Secure Reader	FlexSmart MIFARE Custom Reader	FlexSmart DESFire® Custom Reader
Model Numbers	6075	6076 (formerly Indala MX200)	6077 (formerly Indala DX200)
*Read Range	Up to 2.0" (5.08 cm)		
Mounting	Door mullion or single-gang electrical box		
Dimensions	4.30" H x 1.5" W x 0.72" T (10.9 x 3.8 x 1.8 cm)		
Weight	4 oz. (113 g)		
Style	Slim or Wallswitch		
Read / Write	Read-Only		
Secure Sectors / Files	Sector One	All Sectors	All Files
Formats	HID Only	Custom	Custom
CSN	Yes		
Custom Keys/ Formats	No	Yes	Yes
Audio/Visual	Default state: Beeper on, LED normally red, reader flashes green on card read**		
Power Supply	9-16 VDC (reverse current protected); Linear supply recommended		
Current Requirements	15mA /75mA @ 12VDC; Linear power supply recommended.		
Operating Temperature	-13° to 131° F (-25° to 55° C)		
Operating Humidity	0-95% relative humidity non-condensing		
Transmit Frequency	13.56 MHz		
Cable Distance	Wiegand interface: 500 feet (150 m) 22 AWG; 6 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for connection of all outputs.		
Card Compatibility	<ul style="list-style-type: none"> · HID MIFARE Cards · HID MIFARE key fobs & Tags · HID Proximity and MIFARE Cards (dual technology: MIFARE and HID 125 kHz proximity) · Any Philips compatible MIFARE 1k or MIFARE 4k bytes Cards (ISO 14443, Type A) 	<ul style="list-style-type: none"> · HID or Indala MIFARE Cards · HID or Indala MIFARE key fobs & Tags · HID or Indala Proximity and MIFARE Cards (dual technology: MIFARE and HID 125 kHz proximity) · Any Philips compatible MIFARE 1k or MIFARE 4k bytes Cards (ISO 14443, Type A) 	<ul style="list-style-type: none"> · HID or Indala DESFire Cards · HID or Indala DESFire key fobs & tags · HID or Indala Proximity and DESFire Cards (dual technology: DESFire and HID 125 kHz proximity) · Any Philips compatible DESFire 4k bytes Cards (ISO 14443, Type A)
Certifications	UL 294/cUL (Pending), FCC Certification, United States, Canada Certification, CE Mark, Europe, Australia C-Tick, New Zealand EMC		
Housing Material	Polycarbonate UL 94		
Warranty	Warrantied against defects in materials and workmanship for life (see complete warranty policy for details).		

*Dependent upon installation conditions.

**Consult "How to Order Guide" for other configuration options.

© 2007 HID Global Corporation. All rights reserved. HID, the HID logo, and FlexSmart are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



For best results, please print on recycled paper.

MKT-6076-DS-EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (800) 237-7769
Phone: +1 (949) 598-1600
Fax: +1 (949) 598-1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840