

# FlexSmart® 13.56 MHz Contactless – Readers



**FlexSmart® MIFARE® HID  
Format Secure Keypad  
Reader**

**FlexSmart® MIFARE®  
Custom  
Keypad Reader**

**FlexSmart® DESFire®  
Custom  
Keypad Reader**

**FlexSmart® MIFARE® HID  
Format Secure Reader**

**FlexSmart® MIFARE®  
Custom  
Reader**

**FlexSmart DESFire®  
Custom  
Reader**

Base Model Number	6071	6072	6073	6075	6076 (formerly Indala MX200)	6077 (formerly Indala DX200)
Dimensions	4.7" x 2.9" x 1.1" (11.9 cm x 7.4 cm x 2.8 cm)			4.3" x 1.5" x .72" (10.9 cm x 3.8 cm x 1.8 cm)		
Mounting	Single-gang electrical box			Mullion or Single-gang electrical box		
Power Supply	9-16 VDC (reverse current protected); Linear supply recommended			9-16 VDC (reverse current protected); Linear supply recommended		
Current Requirements	25 mA / 100 mA @ 12 VDC; Linear power supply recommended			15 mA/75 mA @ 12 VDC; Linear power supply recommended		
Termination	Pigtail					
Output Formats	Wiegand or Clock & Data			Wiegand / ABA track II		
Tamper	No					
Indoor/ Outdoor	Both					
Warranty	Lifetime					