

Epic™ Wiegand Reader

Wiegand

Ergonomically designed Wiegand Reader • 315



ACCESS security.

The Epic Wiegand Reader provides an ergonomically designed forward slanted card slot for a more natural hand position when swiping a card. Contemporary styling makes the Epic Wiegand reader a popular choice for both modern and traditional buildings.

The Epic Wiegand reader accepts from 5 to 12 volts input, permitting its use on virtually any system. It is molded of rugged, high impact plastic to resist vandals and epoxy potted to seal out moisture. The Epic Wiegand reader features a tri-color LED. It is immune to external magnetic fields and RF signals.

With next century styling, an ergonomic slot design, and 5 to 12 volt operation, the maintenance free Epic Wiegand reader is the choice of architects, interior designers and industrial relations professionals.

Features

Mounting	The Epic™ reader is back-mounted on a vertical surface, with slot orientation either upward, downward or facing to the left or right.
Visual indication	When a Wiegand card is swiped through the reader, the red LED flashes to green to indicate a proper read. Rejected cards are indicated with an amber color.
Indoor / outdoor design	The Epic Wiegand reader is sealed in a rugged, potted, weatherized polymeric enclosure to withstand harsh environments and provide a high degree of vandal resistance.
Warranty	Epic Wiegand readers are warranted against defects in materials and workmanship for life from date of shipment. (See complete warranty policy for details.)
Part Number	Base Part No.: 315
Description	Tri-state LED
Options	<ul style="list-style-type: none">• Colors (Black or Beige)• Termination (6' cable or barrier strip)• Labels (Black or Custom) (Please see "How to Order" guide for a description of the options and associated part numbers.)

Specifications

For use with code strip layout options:

A - long edge/right side
A1 - long edge/left side
D - short edge

Input power

5-12VDC

Current:

40mA (typical)

Dimensions:

2.66" x 5.86" x 1.50" (6.76 x 14.9 x 3.0 cm)

Slot width:

0.062" to 0.069"
(1.6 mm to 1.75 mm)

Operating temperature:

-40° F to 160° F (-40° C to 70° C)

Operating Humidity:

10 to 95%

Weight:

12.6 oz. (357 gm)

Material:

Long-wearing polymeric plastic

Certifications:

UL 294 listed
CE mark approved

Cable distance:

500 feet (150 m) using 22 GA foil shield cable

© 2007 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 4/2007



For best results, please
print on recycled paper.

MKT-EPIC_DS_EN



ACCESS experience.

hidcorp.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (800) 237-7769
Phone: (949) 598-1600
Fax: (949) 598-1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840