



Working towards the Safer Parking 'Park Mark'

Ideal for compliance with the Safer Parking 'Park Mark' scheme. The external slave Help Point unit is designed to work with any Commend® intercom system.

Manufactured in stainless steel, the welded box section provides a robust, weather-resistant unit. The 'Call' button, also manufactured in stainless steel, prevents any corrosion and acts to maintain a vandal resistant, but aesthetically pleasing unit.

The caller always speaks 'Handsfree' with speech possible from up to 5 meters from the unit, depending on ambient noise levels.

Suitable for all areas where assistance may be required from members of the general public.

Optional Version

- SS201HA - Amplified version for long lines up to 1.8 Km

Technical Data

- Material: Stainless steel, welded
- Colour: Finished in Epoxy Golden Yellow
- Dimensions: Width: 168mm, Height: 258mm, Depth: 98mm
- Fixings: 2 back panel fixing holes accessed by removal of front panel
- Cable Entry: 1 off 20mm plastic compression gland, bottom entry
- Cable Length: SS201H: 300m, 2 pair 0.5mm diameter conductors
SS201HA: 1000m, 5 pair 0.6mm diameter conductors. Line fed power supply
1800m, 5 pair 0.6mm diameter conductors. Local fed power supply
- Power: SS201H: 24V DC 7W max @ 100m line fed
SS201HA 24V DC 4W max @ 100m local supply
- Compliance: BS4800 08 E S1